

## Product Code: EP700G 10-153

## EcoPro G2 600 Litre Upright Glass Door Refrigerated Cabinet



## Features & Benefits

- All new thicker and more robust cabinet design with advanced thermal efficiency and market leading capacity making your money go further
- New 'smartphone style' touch sensitive hidden-until-lit control panel with unique high visibility temperature display combines sophistication with functionality
- All-new ergonomic door and handle design for ease of opening and cleaning
- Designed using high technology: 'Fluid Food-Fresh Dynamics' modelling, the new and improved advanced Foster Circulair II air distribution system maximises efficient operation even when shelves are fully loaded
- Brand-new refrigeration system designed to be the most technologically advanced and energy efficient yet
- Glass door cabinet for easy visibility of stored product, operates up to 32 degrees
- Energy efficiency LED lighting for clear display
- Features Foster's new award-winning +stayclear condenser, revolutionising the effective operation of your refrigeration, ensuring your equipment works more efficiently for longer

External Finish		
s/steel ext, 304 s/s door	Standard	
304 S/S back for island sitting	Option	
Base Fittings		
Castors 80mm	Standard	
Legs 150mm	Option	
Electrical, Service & Ecodesign Data		
230/50/1	Standard	
220/60/1 Electrical Supply	Option	

Internal Finish	
aluminium	Standard
Doors	
Glass	Standard
Left Hand Hinged Door	Option
Product Extras	
Helicoil Mains Lead	Option

Shelving	
Additional S/S Trayslides	Option
Additional GN2/1 Shelf	Option
Refrigeration	
R290 - Energy Efficient	Standard
Integral Refrigeration System	Standard
Less Condensing Unit	Option
Remote Refrigeration System	Option
Specification	
Dimensions (Width)	700
Dimensions (Height)	2080
Dimensions (Depth)	820
Weight (Unpacked, kg)	121
Weight (Packed, kg)	132.6
Gross Volume	600

64.9

Noise Dba @ 1M

## Footnotes

**Fuse Required** 

• Hydrocarbon option not available on glass door models

13

- 32° C ambient on glass door refrigerator model
- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 310mm
- Depth with door open is 1500mm
- Decibel rating measured 1m high from the floor and 1m out from the cabinet











