



The IMC Cirrus 700L Upright Freezer delivers reliable frozen storage for professional kitchens. Compatible with GN 2/1 gastronorm containers, it features ventilated cooling for even temperature distribution and electronic controls for precise temperature management. A durable 304 stainless steel interior and exterior, automatic defrost and condensate evaporation minimise maintenance, while R290 refrigerant and high-performance insulation improve energy efficiency. Supplied on castors with a reversible self-closing door and 24 shelf positions.

AIA FILE NUMBER:

ITEM NUMBER:

PRODUCT FEATURES

- 700L capacity – High-volume frozen storage for busy commercial kitchens.
- GN 2/1 compatible – Designed to accommodate standard gastronorm containers for maximum flexibility.
- Electronic temperature control – Precise temperature management for reliable food storage.
- Ventilated cooling – Even air circulation ensures consistent temperatures throughout.
- 24 shelf positions – Flexible storage to suit a wide range of products.
- 304 stainless steel interior & exterior – Durable, hygienic and easy to clean.
- Rounded internal corners – Improves hygiene with quicker, easier cleaning.
- Automatic defrost – Prevents ice build-up and maintains cooling performance.
- Automatic condensate evaporation – Eliminates the need for manual water disposal.
- Energy-efficient natural refrigerant with low environmental impact.
- High-performance insulation – Retains temperature efficiently to reduce energy consumption.
- Reversible self-closing door – Flexible installation while reducing cold air loss.
- Supplied on castors – Easy to move for cleaning and maintenance.



WEIGHTS & DIMENSIONS

Product Width	683 mm
Product Depth	800 mm
Product Height	2,090 mm
Product Dimensions (WxDxH) (mm)	683 Millimeter X 800 Millimeter X 2090 Millimeter

SHIPPING DETAILS

Ship Width	74 cm
Ship Depth	85 cm
Ship Height	228 cm
Ship Weight	122 kg
Shipping Package Type	Pieces

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V
Electrical Volts Icon	230V
Electrical Phase Icon	1PH

ADDITIONAL TECHNICAL SPECIFICATIONS

Capacity (Volume)	700
Door Material	Solid
Number of Shelves	3
Temperature Minimum	-25

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

