





- **XTRA** Value
- **XTRA** Reliability
- **Foster** Service





The XTRA range is specifically built to provide a perfect, affordable and reliable, commercial refrigeration solution designed to fit with your budget, and that's not all. XTRA comes with full after care support giving you one less thing to worry about.





Gastronorm Cabinets
600/1300 litre capacities



Slimline Cabinet 400 litre capacity



Gastronorm Counters
2 and 3 door models




Economic Blast Chillers 10, 20 and 35 kg chilling capacities





More...for less! XTRA cabinets at-a-glance

- 500/1300 Litre capacities
- Stainless Steel
- Adjustable GN 2/1
 Shelving
- Energy Efficient R290
 Refrigerant



New rear air channel makes sure the cold air gets to your food





Refrigeration system maintains cabinet storage temperature in hot kitchens



Gastronorm shelving is supplied with both sizes of cabinets, 3 for the 600 litre model and 6 for the 1300



Microprocessor controller provides simple accurate temperature control





- Removable Gasket Door
- Fan Assisted Cooling
- Fully Automatic
- 2 Years Parts & Labour Warranty









1390 x 850 x 1985

External Dimensions (w x d x h) mm

Temperature

Exterior Finish

50 >	198	5		6

Refrigerator +2/+8°C

Stainless Steel

675 x 850 x 1985	1390 x 850 x 1985
XR600L	XR1300H
Freezer -18/-21*C	Refrigerator +2/+8*C
Stainless Steel	Stainless Steel
Aluminium	Aluminium
600	1300
2	

XR1300L
Freezer -18/-21°C
Stainless Steel
Aluminium
1300
6
Castors
Standard

Interior Finish	Aluminium	Aluminium	Aluminium	Aluminium
Gross Volume (litres)	600	600	1300	1300
Gastronorm 2/1 Shelves (on trayslides)	3	3	6	6
Base Fittings	Castors	Castors	Castors	Castors
Removable Gasket	Standard	Standard	Standard	Standard
Door Lock(s)	Standard	Standard	Standard	Standard
Reversible Door	Yes	Yes	N/A	N/A
Refrigerant	R290	R290	R290	R290
Optional Refrigerant	R134a	R404a	R134a	R404a
Power Supply (230/1/50)	10amp	10amp	10amp	10amp
Energy Grade	D (R290) / D (R134a)	D (R290) / G (R404a)	E (R290) / E (R134α)	E (R290) / G (R404a)



Slimline Cabinets



- Slimline Footprint
- Stainless Steel
- Energy Efficient R290 Refrigerant
- 2 Years Parts & Labour Warranty



Refrigerant







External Dimensions (w x d x h) mm 600 x 660 x 1875 600 x 660 x 1875 600 x 660 x 1875 XR415G XR415L Temperature Exterior Finish Stainless Steel Stainless Steel Stainless Steel Interior Finish Aluminium Aluminium Aluminium Gross Volume (Litres) 400 400 400 Door Solid Glass Solid Standard Standard Standard Refrigerant R290 R290 R290 (no light) Optional Refrigerant R134a R134a R134a No. of Shelves 6 (Fixed) 480 x 420 480 x 420 480 x 420 Shelf Size (mm) Removable Gasket Yes Yes Yes No Lighting Option No Yes Fixed Roller Castors (to rear) Standard Standard Standard Levelling Feet (to front) Standard Standard E (R290) / G (R134a) Energy Grade

[†] Product type is not currently regulated by Ecodesign



Glass door option also available (ambient operation up to 25°C)



XR415H interior with 4 x Nylon coated wire shelves (480 x 420mm)



Microprocessor controller provides simple accurate temperature control



Counter Storage



- Stainless Steel
- Energy Efficient R290 Refrigerant
- Fan Assisted Cooling
- 2 Years Parts & Labour Warranty



XR2H refrigerated counter



External Dimensions (w x d x h) mm	1330 x 700 x 855	1775 x 700 x 855	
Model	XR2H	XR3H	
Temperature	Refrigerator +2/+8°C	Refrigerator +2/+8°C	
Exterior Finish	Stainless Steel	Stainless Steel	
Interior Finish	Aluminium	Aluminium	
Gastronorm 1/1 Shelves (on trayslides)	2	3	
Base Fittings	Castors	Castors	
Removable Gasket	Standard	Standard	
100mm Splashback	Option	Option	
Basket Drawers	Option	Option	
Rear Cover (stainless)	Option	Option	
Refrigerant	R290	R290	
Optional Refrigerant	R134a	R134a	
Power Supply (230/1/50)	10amp	10amp	
Energy Grade	C (R290) / D (R134a)	C (R290) / D (R134a)	



Refrigeration system maintains counter storage temperature in hot kitchens



Basket drawers option allows storage flexibility



Microprocessor controller provides simple accurate temperature control





Economic Blast Chilling











- Energy Efficient R290 Refrigerant
- Stainless Steel
- Hard & Soft Chill Options
- 2 Years Parts & Labour Warranty

Blast Chillers







External Dimensions (w x d x h) mm	755 x 700 x 880	755 x 700 x 880	755 x 700 x 1535
Model	XR10	XR20	XR35
Interior/Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel
Chilling Capacity (kg)	10	20	35
GN 1/1 Shelves Positions	5	5	10
Base Fittings	Castors	Castors	Castors
Removable Gasket	Standard	Standard	Standard
Refrigerant	R290	R290	R290
Optional Refrigerant	R404a	R404a	R404a
Power Supply (230/1/50)	13amp	13amp	13amp
Energy Grade	†	†	†

† Product type is not currently regulated by Ecodesign



75mm shelf spacing maximises capacity



No visible screws or dirt traps for ease of cleaning

A Division of ITW Ltd

Foster Refrigerator, Oldmedow Road, King's Lynn Norfolk PE30 4JU United Kingdom To discuss your options or to find out more:

Call: +44 (0)843 216 8800 Fax: +44 (0)843 216 4700 Email: info@foster-uk.com Visit: fosterrefrigerator.com

We reserve the right to change specifications without notice. Literature Code 1725B