



Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- OA8917/C Lincat Opus 800 Free-standing Floor Stand with Castors - for units W 600 mm
- OA8917 Lincat Opus 800 Free-standing Floor Stand with Legs - for units W 600 mm
- OA8972/C Lincat Opus 800 Free-standing Pedestal with Doors and Castors - for units W 600 mm
- OA8972 Lincat Opus 800 Free-standing Pedestal with Doors and Legs - for units W 600 mm
- LK11 OPUS 800 LONG LEG KIT

PRODUCT FEATURES

- Chrome surface heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system
- Transfers heat to food more efficiently than a standard griddle
- Two separately controlled heat zones give you the option of operating either zone independently to provide a smaller cooking area during quiet periods as well as offering versatility when cooking two separate meals simultaneously
- Precise thermostatic control up to 300°C for consistent results and economical operation

Designed for quality cooking at speed, the Opus 800 Electric Chrome Griddle heats up quicker than standard griddles with less energy loss as well as reduced energy radiation, keeping the kitchen cooler for staff and reducing pressure on the ventilation system. Not only is heat transferred more efficiently than with a standard griddle, but the precise thermostatic control up to 300°C means that you're always in control, whether your cooking meat, eggs or vegetables. Perfect for any busy commercial kitchen, the chrome griddle comes with two separately controlled heat zones, which allow for the versatility of operating either zone independently when cooking two separate meals simultaneously.

WEIGHTS & DIMENSIONS

| | |
|--------|---------|
| Width | 600 mil |
| Depth | 800 mil |
| Height | 428 mil |
| Weight | 81.5 kg |

SHIPPING DETAILS

| | |
|----------------------------|-------------------------|
| Ship Width | 70 cm |
| Ship Depth | 85 cm |
| Ship Height | 63 cm |
| Ship Weight | 89.65 kg |
| Number of Shipment Parcels | 1 |
| Shipping Origin Zip Code | LN6 3QZ, UNITED KINGDOM |
| Quick Ship Product | No |
| Returnable Item | No |

PRODUCT CERTIFICATIONS



ENERGY SPECS

| | | | |
|----------------------------|--|--------------------------------------|------------------|
| Primary Energy Source Type | Electricity | Number of Electrical Conductor Wires | 1 |
| Electrical Amps | Single Phase 34.8/Three Phase L1=17.4; L2=17.4; L3=N/A | Electrical Connection Type | Direct Hardwired |
| Electrical Voltage | 230 volts/400 volts | Electrical Plug Type | Hardwired |
| Electrical Watts | 8000 | Number of Electrical Plugs | Not Applicable |
| Electrical Phase | Single, Three | Dedicated Circuit Required | Yes |
| Kilowatts | 8 kW | Energy Saving | No |

ADDITIONAL SPECIFICATIONS

| | | | |
|--|--|-----------------------------|-------------------|
| Control Type | Rotary Control Knob | Number Of Controls | 2 |
| Cooking Area Plate Depth | 600 mm | Number of Heating Zones | 2 |
| Cooking Area Plate Width | 590 mm | Plate Shape | Rectangle |
| Cooking Plate Finish Material Type | Chrome Plated | Plate Thickness | 15 mm |
| Food Production Rate | 128 x 225g [8oz] steaks [chilled] per hour | Temperature Maximum | 300 °C |
| Legs or Casters | Not Applicable | Temperature Minimum | 90 °C |
| Lower Platen Surface Type (multi-select) | Smooth | Thermostat Element Location | Under Plate Mount |

BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING

