

### FOUR COOKING ZONE INDUCTION RANGE





### **MODELS and ACCESSORIES**

E3913i - 4 x 3.5kW Four zone induction range with fan-assisted oven
E3914i - 4 x 5kW Four zone induction range with fan-assisted oven

- Fully integrated extended flue
- Factory fitted, adjustable castors
- Fixed installation kit
- Suiting kit

### **KEY FEATURES**

- 4 x 270mm diameter, energy efficient heat zones
  - Instant on, fast heat up, reduced energy usage
- Heavy duty, ceramic glass hob plate
  - Spillages can simply be wiped away
- Variable control settings
  - Fast, controllable cooking
- In-built pan detection
  - No pan = no wasted energy
- Fan-assisted, 1/1 gastronorm compatible oven
  - 5 shelf positions provide 2 shelf operation
- Glass panels in oven doors
  - Monitor cooking without losing valuable heat
- Low profile door handles
  - Reduces intrusion into work space
- Laser-etched control icons
  - Permanent, indelible markings

### **INSTALLATION NOTES**

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.







# **DOMINATORPLUS**

## FOUR COOKING ZONE INDUCTION RANGE

## **MODEL DIMENSIONS** (in mm)







Height on castors is identical

### **SPECIFICATION DETAILS**

	E3913i	E3914i
Electrical rating (kW)	20	26
Electrical supply voltage	400V 3N~	400V 3N~
Required electrical supply 400V 3N~ (amps)	32	63
Electrical current split (amps)	L1: 29 / L2: 29 / L3: 29	L1: 38 / L2: 38 / L3: 38
Hotplate rating (kW)	3.5 x 4	5 x 4
Oven element rating (kW)	6	6
Oven dimensions (w x d x h - mm)	530 x 536 x 380	530 x 536 x 380
Oven shelf (w x d - mm)	530 x 536	530 x 536
Gastronorm compatibility	1/1	1/1
Weight (kg)	140	140
Packed weight (kg)	160	160

