



## UR400SG

### Glass Door Merchandiser

#### Product Features

- Fully automatic
- Fan assisted cooling
- Electronic thermostat
- Digital controller and temperature display
- Reversible door
- Adjustable shelves
- LED interior light with switch
- Adjustable feet with rollers to rear

The UR400G range is available in a white or stainless steel exterior finish to suit your requirement and features a sturdy aluminium door frame. Developed from the solid door UR400 that has a reputation for quality and reliability, this glass door option has fan assisted cooling and vertical LED lighting within the door frame to help create an excellent display for your produce. A digital temperature display and controller help ensure ease of use and reliability.

#### Measures and Content

|                    |                |           |
|--------------------|----------------|-----------|
| Total Display Area | m <sup>2</sup> | 0.75      |
| Temperature Range  | °C             | +2 to +10 |
| Climate Class      |                | 4         |
| Gross / Net Weight | kg             | 85 / 80   |
| Gross / Net Volume | l              | 374 / 350 |

#### Design and Material

|                         |                      |     |
|-------------------------|----------------------|-----|
| Door Number & Type      | 1 hinged glass door  |     |
| Tempered glass          | Yes                  |     |
| Door Reversible         | Yes                  |     |
| Shelves Number & Type   | 4 wire shelves white |     |
| Shelf Color             | White                |     |
| Shelf Dimensions        | 505 x 415 mm         |     |
| Bottom Shelf Dimensions | 505 x 220            |     |
| Max load on Shelves     | kg/m <sup>2</sup>    | 110 |
| Feet / Legs             | 4 adjustable feet    |     |
| Castors                 | 2 rollers            |     |
| Exterior Finish         | SS430                |     |
| Interior Finish         | White ABS            |     |
| Interior Light          | LED Cold white       |     |
| Lock                    | Yes                  |     |

#### Cooling and Functions

|                    |              |    |
|--------------------|--------------|----|
| Type of Controller | Electronic   |    |
| Type of Cooling    | Fan assisted |    |
| Type of Defrost    | Automatic    |    |
| Refrigerant        | R600a        |    |
| Refrigerant Charge | g            | 75 |
| Thermometer        | Yes          |    |

#### Power and Consumption

|                           |                |            |
|---------------------------|----------------|------------|
| Energy Class              | B              |            |
| Energy Consumption        | kWh/24h        | 2.12       |
| Annual Energy Consumption | kWh/year       | 773        |
| Power                     | 13 Amp         |            |
| Max Ambient               | 30°C at 55% RH |            |
| Input Power               | W              | 130        |
| Voltage / Frequency       | V/Hz           | 220-240/50 |
| Noise Level               | dB(A)          | 40         |

#### Dimensions

|                            |     |                  |
|----------------------------|-----|------------------|
| Internal Dimension (WxDxH) | mm  | 506 x 485 x 1620 |
| External Dimension (WxDxH) | mm  | 600 x 585 x 1855 |
| Packed Dimension (WxDxH)   | mm  | 690 x 650 x 2050 |
| 40ft Container Load        | pcs | 54               |



Internal fan



Strong handle