

# ecomax™

by **HOBART**



## PASSTHROUGH DISHWASHERS

H602



### You need...

- ✓ Value for money...
- ✓ No costly vent canopy or extraction...
- ✓ Economical operation...
- ✓ Flexible for whatever your kitchen needs...
- ✓ Fast performance...
- ✓ A hygienic wash result...
- ✓ A cleaner, more efficient machine...
- ✓ Easy to use so fewer operator mistakes...
- ✓ Simple installation...
- ✓ Low price...
- ✓ Cleaner wash water ...
- ✓ Consistent performance...
- ✓ Fully compliant...
- ✓ Softer water for a better wash result...

### ecomax delivers...

- all-in-one economical solution providing a powerful wash
- unique 4 sided fully enclosed hood that prevents heat and steam escaping and saves energy
- compact 23 litre wash tank, quick to fill and low running costs
- suitable for straight through or corner operation
- washes up to 48 racks per hour (850 plates per hour)
- thermostop rinse control ensures the machine will only rinse at the correct temperature
- integral detergent and rinse aid dosing equipment as standard
- simple electronic control with digital temperature display
- fitted with drain pump and rinse booster pump as standard
- high performance
- effective filtration system fitted as standard on all machines
- wash arms fitted with indented anti-block jets
- Class A air gap as standard ensuring dirty dish water doesn't siphon back into the mains water
- optional integrated water softener available

Tel: 0870 168 8881

[www.hobartindependent.co.uk](http://www.hobartindependent.co.uk)

# PASSTHROUGH DISHWASHERS

## Specifications

### H602

#### GENERAL

Dimensions	740mm(w) 635mm(d) 1960mm(h)
Height hood open	1960mm(h)
Width with handle	713mm
Number of racks	1 x plate rack 1 x cutlery basket
Loading height	440mm
Rack size	500 x 500mm
Max plates per rack	18
Max racks p/h	48
Net weight (kg)	100
Rinse booster pump	YES
Built in detergent dispenser	YES
Built in rinse aid dispenser	YES

#### Controls

Class A air gap	YES
Thermostop control	YES
Programme times, secs	75 – 150
Water consumption/cycle	2.9L
Wash tank capacity	23L
Wash tank heating	2.5kW
Rinse tank capacity	5.6L
Rinse booster heating	6.2kW
Drain pump	YES
Wash pump rating	0.4kW
Wash pump flow rate	225L/min
Rinse pump rating	0.27kW
Rinse pump flow rate	20L/min
Noise level (dB)	61

#### WATER

Water pressure	0.8 – 6 BAR
Water temp	MAX 60°C

#### ELECTRIC

Voltage 3P	400/50/3
Voltage 1P	230/50/1
Total loading 3P	(Factory setting) 3 x 16A/6.2kW
Total loading 1P	25A/4.6kW



TECHNICAL DETAILS MAY BE SUBJECT TO CHANGE AT ANY TIME WITHOUT PRIOR NOTICE.

#### HOBART INDEPENDENT

Southgate Way, Orton Southgate,  
Peterborough, PE2 6GN

**0870 168 8881**

or visit [www.hobartindependent.co.uk](http://www.hobartindependent.co.uk)

**ecomax**<sup>TM</sup>

by **HOBART**