

# ECOMAX OR ECOMAX PLUS – IT'S YOUR CHOICE!





The entry-level models for those who search for a low-cost dishwasher for commercial use. Ideal for start-ups and companies with irregular washing frequency, which invest in a dishwasher for the first time. **ecomax** meets all requirements for hygienic wash results.



For mid-tier operators who seek a plus in comfort and equipment. **ecomax plus** combines all the features of a **ecomax** dishwasher and offers a plus in wash power, energy efficiency, noise reduction and ease of use.



## **OVERVIEW OF OUR MODELS**

made in germany



Model G404 / G404 S Compact glasswasher





Model G504 / G504 S Glasswasher



Model F504 / F504 S Undercounter dishwasher



Model H602 / H602 S Hood-type dishwasher





Model G503 / G503 S

Glasswasher



Model F503 / F503 S

Undercounter dishwasher



Model H603 / H603 S

Hood-type dishwasher







## **ECOMAX G404 COMPACT GLASSWASHER**

The fast and reliable glasswasher in compact design. Perfect for start-ups, small bars or restaurants.

#### **FEATURES**

- Electronic control with digital temperature indication for easy operation
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Integrated counter for cycles and water consumption, e.g. for control of water treatment system
- Deep drawn rack track for easy cleaning

- Incl. connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self flushing programme to maintain hygiene within the machine
- S Version fully equipped with rinse pressure pump, class A air gap, both models with detergent and rinse aid dispenser and drain pump.









## **ECOMAX PLUS G403**

#### **COMPACT GLASSWASHER**

The compact glasswasher for hotels, bars and restaurants, which are washing more than hundred glasses a day.

#### **plusFEATURES**



- + Deep-drawn wash tank for easy cleaning
- + Better energy efficiency saves operating costs
- + Double-walled housing and heat insulated front door for reduction of noise and energy losses
- + Tank strainer, coarse filter and pump suction casing secure safe operation
- + Door damping control for long life operation
- + Fully equipped with rinse pressure pump
- Optional cabinet base for ergonomic operation











With a high capacity of up to 60 racks per hour, this dishwasher is a reliable partner for club houses, bistros, and fast-food restaurants. The practical floor unit fits under every work counter.

#### **FEATURES**

- Electronic control with digital temperature indication for easy operation
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Integrated counter for cycles and water consumption, e.g. for control of water treatment system
- Deep drawn rack track for easy cleaning

- Incl. connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self flushing programme to maintain hygiene within the machine.
- Tank strainer reduces soiling of the tank water
- Optional cabinet base for ergonomic operation
- Fully equipped with rinse pressure pump, class A air gap, detergent and rinse aid dispenser and drain pump.









Due to the high wash power, the double-walled housing and the robust filter systems, it is the quiet and resource-saving solution for your busy workaday life.



- + Deep-drawn wash tank for easy cleaning
- + Better energy efficiency saves operating costs
- + Double-walled housing and heat insulated front door for reduction of noise and energy losses
- + Coarse filter secures safe operation

+ Door damping control for long life operation

comax slus 1 2 11 7 7

+ Fully equipped with rinse pressure pump









#### **ECOMAX H602**

#### **HOOD-TYPE DISHWASHER**

The dishwasher for ergonomic and efficient work processes in the kitchen. Combined with tables, it is a powerful partner for the catering and hotel sector.

#### **FEATURES**

- The 4-sided closed hood keeps energy and humidity in the system and saves up to 3 kW energy
- Deep-drawn wash tank for easy cleaning
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Incl. connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self flushing programme to maintain hygiene within the machine
- Fully equipped with rinse pressure pump, detergent and rinse aid dispenser and drain pump.









### **ECOMAX PLUS H603**

### **HOOD-TYPE DISHWASHER**

The dishwasher for ergonomic and efficient work processes in the kitchen. Combined with tables, it is a powerful partner for the catering and hotel sector.

#### plusFEATURES

+++ additional to ecomax +++

- + Stronger wash pump for best wash results
- + Shorter cycle times for higher capacities
- + All around ergonomic handle










# LOW PRICE HIGH PERFORMANCE




## **DRAWINGS**




#### Glasswasher model G404



## Glasswasher model G504 Undercounter dishwasher model F504




#### Hood-type dishwasher model H602



① Drain hose ② Supply hose ③ Connection cable ④ Liquid detergent  $^{a)}$  ⑤ Rinse aid  $^{a)}$  depending on the device chemical dispensers are not included


## ecomax plus

#### Glasswasher model G403




#### Glasswasher model G503

#### **Undercounter dishwasher model F503**



#### Hood-type dishwasher model H603



## **FEATURES**



|  | GLASSWASHER |              |             | plus         |             |              |             |              |
|--|-------------|--------------|-------------|--------------|-------------|--------------|-------------|--------------|
| MODELS   | G404<br>-12 | G404<br>S-12 | G504<br>-10 | G504<br>S-10 | G403<br>-11 | G403<br>S-11 | G503<br>-11 | G503<br>S-11 |
| Integrated water softener*                     | -           | •            | -           | •            | -           | •            | -           | •            |
| External water treatment system**              | -           | -            | 0           | 0            | 0           | 0            | 0           | 0            |
| Double-walled housing                          | -           | -            | -           | -            | •           | •            | •           | •            |
| Deep-drawn wash tank                           | -           | -            | -           | -            | •           | •            | •           | •            |
| Door damping control                           | -           | -            | -           | -            | •           | •            | •           | •            |
| Tank strainer                                  | -           | -            | •           | •            | •           | •            | •           | •            |
| Drain pump                                     | •           | •            | •           | •            | •           | •            | •           | •            |
| Rinse pressure pump***                         | _           | •            | •           | •            | •           | •            | •           | •            |
| Rinse aid dispenser                            | •           | •            | •           | •            | •           | •            | •           | •            |
| Detergent dispenser                            | •           | •            | •           | •            | •           | •            | •           | •            |
| Base cabinet (435 mm high) with removable door | -           | -            | 0           | 0            | 0           | 0            | 0           | 0            |
| Glass rack (sloped rows)                       | •           | •            | •           | •            | •           | •            | •           | •            |
| Glass rack (flat)                              | _           | -            | -           | -            | •           | •            | -           | _            |
| Cutlery box CB1                                | •           | •            | •           | •            | _           | -            | _           | -            |

O Optional

<sup>\*</sup> For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water treatment system.

 $<sup>^{\</sup>star\star}$  For use of an external water treatment system, an integrated rinse pressure pump is necessary.

<sup>\*\*\*</sup> Necessary flow pressure without rinse pressure pump: 2 - 6 bar. Flow pressure with integrated rinse pressure pump: 0.8 - 6 bar.

Inclusive

## **FEATURES**

made in germany

|  | UNDERCOUNTER DISHWASHER plus |              | HOOD-TYPE<br>DISHWASHER |              | plus        |              |              |               |
|--|------------------------------|--------------|-------------------------|--------------|-------------|--------------|--------------|---------------|
| MODELS   | F504<br>-20                  | F504<br>S-20 | F503<br>-11             | F503<br>S-11 | H602<br>-12 | H602<br>S-12 | H603<br>-10A | H603<br>S-10A |
| Integrated water softener*                     | -                            | •            | -                       | •            | -           | •            | -            | •             |
| External water treatment system**              | 0                            | -            | 0                       | -            | 0           | -            | 0            | 0             |
| Double-walled housing                          | _                            | -            | •                       | •            | -           | -            | _            | _             |
| Deep-drawn wash tank                           | _                            | -            | •                       | •            | •           | •            | •            | •             |
| Door damping control                           | -                            | -            | •                       | •            | -           | -            | -            | -             |
| Tank strainer                                  | •                            | •            | •                       | •            | •           | •            | •            | •             |
| Drain pump                                     | •                            | •            | •                       | •            | •           | •            | •            | •             |
| Rinse pressure pump***                         | •                            | •            | •                       | •            | •           | •            | •            | •             |
| Rinse aid dispenser                            | •                            | •            | •                       | •            | •           | •            | •            | •             |
| Detergent dispenser                            | •                            | •            | •                       | •            | •           | •            | •            | •             |
| HOBART tabling programme                       | -                            | -            | -                       | -            | 0           | 0            | 0            | 0             |
| Base cabinet (435 mm high) with removable door | 0                            | 0            | 0                       | 0            | -           | -            | -            | -             |
| Plate rack P-18-12                             | •                            | •            | •                       | •            | •           | •            | •            | •             |
| Cutlery box CB1                                | •                            | •            | -                       | -            | •           | •            | _            | -             |
| Cutlery rack with 4 boxes CB4                  | -                            | -            | •                       | •            | -           | -            | -            | -             |
| Universal flat rack B-00-07                    | _                            | -            | •                       | •            | _           | _            | •            | •             |
| Cutlery rack with 8 boxes CB8                  | -                            | _            | _                       | _            | -           | _            | •            | •             |

## **TECHNICAL SPECIFICATIONS**



|                      | <b>ecomax</b> <sup>™</sup> by HOBART |                                 |                                 |                                 |
|----------------------|--------------------------------------|---------------------------------|---------------------------------|---------------------------------|
| MODELS               | G404                                 | G504                            | F504                            | H602                            |
| Rack capacity        | 60 /h                                | 60 /h                           | 60 /h                           | 45 /h                           |
| Tank capacity        | 10 I                                 | 25 I                            | 25 I                            | 21 I                            |
| Water consumption    | 2.0 l/rack                           | 2.3 I/rack                      | 2.3 l/rack                      | 2.8 l/rack                      |
| Wash pump            | 0.18 kW                              | 0.34 kW                         | 0.34 kW                         | 0.4 kW                          |
| Tank heating         | 1.8 kW                               | 1.8 kW                          | 1.8 kW                          | 2.5 kW                          |
| BOOSTER LOADING      |                                      |                                 |                                 |                                 |
| Standard             | 1.9 kW (230 V)                       | 3.7 kW (230 V)                  | 3.7 kW (230 V)                  | 6.2 kW (400 V)                  |
| Alternative          | 5.6 kW (400 V)                       | 5.6 kW (400 V)                  | 5.6 kW (400 V)                  | 4.1 kW (230 V)                  |
| Alternative 2        | 3.7 kW (230 V)                       | 1.9 kW (230 V)                  | 1.9 kW (230 V)                  | -                               |
| TOTAL CONNECTED LOAD |                                      |                                 |                                 |                                 |
| Standard             | 2.1 kW (230 V)                       | 4.1 kW (230 V)                  | 4.1 kW (230 V)                  | 6.6 kW (400 V)                  |
| Alternative          | 5.8 kW (400 V)                       | 5.9 kW (400 V)                  | 5.9 kW (400 V)                  | 4.6 kW (230 V)                  |
| Alternative 2        | 3.9 kW (230 V)                       | 2.2 kW (230 V)                  | 2.2 kW (230 V)                  | -                               |
| Rated voltage        | 230 / 50 / 1<br>(400 / 50 / 3N)      | 230 / 50 / 1<br>(400 / 50 / 3N) | 230 / 50 / 1<br>(400 / 50 / 3N) | 400 / 50 / 3N<br>(230 / 50 / 1) |
| Width                | 436 mm                               | 576 mm                          | 576 mm                          | 635 mm                          |
| Depth                | 534 mm                               | 604 mm                          | 604 mm                          | 742 mm                          |
| Height               | 700 mm                               | 820 mm                          | 820 mm                          | 1.480 (1.960) mm                |
| Loading height       | 308 mm                               | 360 mm                          | 360 mm                          | 440 mm                          |
| Rack size            | 390 x 390 mm                         | 500 x 500 mm                    | 500 x 500 mm                    | 500 x 500 mm                    |

<sup>\*</sup> The machine is equipped with an automatic cycle-time control which ensures hygienic rinse temperatures even on a cold-water supply or with reduced heating performance.

## **TECHNICAL SPECIFICATIONS**



|                      | ecomax plus                     |                                 |                                 |                                 |  |  |
|----------------------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|--|--|
| MODELS               | G403                            | G503                            | F503                            | H603                            |  |  |
| Rack capacity        | 40 /h                           | 40 /h                           | 40 /h                           | 55 /h                           |  |  |
| Tank capacity        | 81                              | 10.6 l                          | 10.6 l                          | 23                              |  |  |
| Water consumption    | 2.5 l/rack                      | 2.8 l/rack                      | 2.8 l/rack                      | 2.8 l/rack                      |  |  |
| Wash pump            | 0.6 kW                          | 0.6 kW                          | 0.6 kW                          | 0.7 kW                          |  |  |
| Tank heating         | 0.8 kW                          | 0.8 kW                          | 0.8 kW                          | 2.5 kW                          |  |  |
| BOOSTER LOADING      |                                 |                                 |                                 |                                 |  |  |
| Standard             | 2.8 kW (230 V)                  | 4.1 kW (230 V)                  | 6.2 kW (400 V)                  | 6.2 kW (400 V)                  |  |  |
| Alternative          | 4.2 kW (400 V)                  | 6.2 kW (400 V)                  | 2.1 kW (230 V)                  | 4.1 kW (230 V)                  |  |  |
| Alternative 2        | 2.8 kW (230 V)                  | 1.4 kW (230 V)                  | 1.4 kW (230 V)                  | _                               |  |  |
| TOTAL CONNECTED LOAD |                                 |                                 |                                 |                                 |  |  |
| Standard             | 3.2 kW (230 V)                  | 5.7 kW (230 V)                  | 5.7 kW (230 V)                  | 7 kW (400 V)                    |  |  |
| Alternative          | 5.4 kW (400 V)                  | 7.7 kW (400 V)                  | 7.7 kW (400 V)                  | 4.9 kW (230 V)                  |  |  |
| Alternative 2        | 4.1 kW (230 V)                  | 2.9 kW (230 V)                  | 2.9 kW (230 V)                  | -                               |  |  |
| Rated voltage        | 230 / 50 / 1<br>(400 / 50 / 3N) | 230 / 50 / 1<br>(400 / 50 / 3N) | 400 / 50 / 3N<br>(230 / 50 / 1) | 400 / 50 / 3N<br>(230 / 50 / 1) |  |  |
| Width                | 460 mm                          | 600 mm                          | 600 mm                          | 635 mm                          |  |  |
| Depth                | 590 mm                          | 600 mm                          | 600 mm                          | 742 mm                          |  |  |
| Height               | 700 mm                          | 820 mm                          | 820 mm                          | 1.480 (1.960) mm                |  |  |
| Loading height       | 315 mm                          | 425 mm                          | 425 mm                          | 440 mm                          |  |  |
| Rack size            | 400 x 400 mm                    | 500 x 500 mm                    | 500 x 500 mm                    | 500 x 500 mm                    |  |  |





A registered brand of HOBART GmbH A company of the *ITW* Group

UNITED KINGDOM · HOBART UK
Southgate Way · Orton Southgate · Peterborough I PE2 6GN
Phone: +44(0)870 168 8881 · customer.support@hobartuk.com
www.hobartuk.com

www.hobartindependent.co.uk

made in germany