



# GRAM GASTRO K 2207 CSG A DL/DL/DL/3D L2

Product series: Gastro

Item number: 952200501

The GRAM GASTRO K 2207 CSG A DL/DL/DL/3D L2 is a with a net internal volume of 359 Ltr.

GRAM Gastro 07 is a series of 1/1 GN workstations, equipped with customizable sections. Furthermore, the highly modular refrigerated counter offers an abundance of practical configuration possibilities.



## Temperature Control

Thanks to the Gram air distribution system, temperatures inside the counters always maintain a uniform and correct level.

This includes rapid temperature recovery after every door opening.

## Modularity & Scalability

With GRAM GASTRO 07 counters you can put together your individual workplace. Choose your combination of worktop, doors, and drawers, legs / castors/electric elevation, temperature ranges and accessories.

## Easy Maintenance

A compact slide-out refrigeration unit for easy maintenance and service access. Removable and easy to clean condenser filters and gaskets.

## High Standard in Hygiene

- The counter almost entirely consists of smooth surfaces – the perfect design for easy, quick and thorough cleaning.
- 'Drip Nose' edges on worktops to prevent the ingress of water.
- Worktops with splashbacks to protect your counter from spillage.
- Removable drawer and door gaskets for easy cleaning.
- Pan-shaped inside base with rounded corners to catches fluid.

## Allergy-Proof

Counters are made from nickel-free stainless steel.

## Ergonomic and practical design

- Anti-tilt shelves and drawers with pull-out stop.
- Extra-long telescopic rails on drawers - GN trays can be lifted in and out without tilting.

## SPECIFICATIONS

Temperature range	+2/+12°C	Connection load (Watt)	190
Volume, gross (ltr.)	668	Energy consumption (kWh/Year)	652
Net usable volume (ltr.)	359	Energy Efficiency Class (ISO 22041-2019)	A
Exterior	Stainless	Energy Efficiency Index EEI	24.06
Interior	Stainless	Climate class	5
Dimensions W x D x H (mm)	2163 x 719 x 885/950	Legs / Castors	H = 135/200 mm (L2)
Weight, packed (kg)	221	Refrigerant (kg)	0.097
Insulation (mm)	50 mm (cyclopentane)	CO2 equivalent (kg)	0.291
Refrigerant	R290	GN or Shelf size	1/1 GN
GWP	3	Number of shelves	6
Ref. capacity at -10°C (Watt)	406	Equipped with	Stainless steel solid top, 3 door sections each with 2 stainless shelves and 1 drawer section with 3 x 1/3 drawers
Connection	230V, 50 Hz	Door Type	Solid Door