



The Refrigeration Experts

## Product specification

---



### EP700H: 600 Ltr Cabinet Refrigerator

41-102

- ✓ Best seller. Trusted by Michelin Star chefs
- ✓ Award-winning low energy technology
- ✓ In-built safety and hygiene features
- ✓ Only costs approx. 20p/day to run

#### About the product

Explore the entire award-winning, energy saving [fridge](#) and [freezer](#) range.

## Why choose this product

- New and improved +stayclear condenser increases product life and reduce energy consumption. Award winning technology from the Refrigeration Experts
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage, even when fully loaded
- The controller display uses pure LEDs, incorporating InGaN technology, achieving high, long lasting resolution – while using less power
- Gold standard in performance stainless steel used on all doors and unit covers for G3 – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity with 4 shelves, making your money go further – holds more than a conventional fridge
- Operates efficiently in ambient temperatures of up to 43°C

## Specification

Technical		Dimensions	
<b>Temperature</b>	Refrigerator +1/+4°C	<b>Height (mm)</b>	2080
<b>Thermal heat rejection (W)</b>	140	<b>Width (mm)</b>	700
<b>Electrical supply</b>	230/50/1	<b>Depth (mm)</b>	855
<b>Current (A)</b>	0.6	<b>Gross volume (ltr)</b>	600
<b>Power (W)</b>	140	<b>Net volume (ltr)</b>	479.9
<b>Refrigerant mass (g)</b>	95	<b>GN size</b>	2/1
<b>Refrigerant</b>	R290	<b>Gross weight (kg)</b>	109.5
<b>Fuse rating (A)</b>	10	<b>Net weight (kg)</b>	99.5

Build		Energy	
<b>Cabinet type</b>	Standard	<b>Climate Class</b>	5
<b>Finish ext/int</b>	S/S & Alu	<b>Energy grade</b>	A
<b>Number of sections</b>	1	<b>EEI</b>	18.81
<b>Section configuration</b>	Right hinge	<b>AEC (kWh)</b>	262.8
<b>System</b>	Integral	<b>GWP</b>	3
<b>Leg type</b>	Braked castors	<b>Energy consumption (kWh/24hr)</b>	0.72

#### Footnotes

- Castors are not available if product is supplied less condensing unit
- 100mm clearance is required above the cabinet to allow for adequate airflow and service access
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | [sales@foster-gamko.com](mailto:sales@foster-gamko.com) | [www.fosterrefrigerator.com](http://www.fosterrefrigerator.com)

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.