


LINCAT FILTERFLOW COUNTER-TOP AUTOMATIC FILL PUSH-BUTTON WATER BOILER - W 250 MM - 3.0 KW

MODEL: EB3FX/PB







PRODUCT OPTIONS AND ACCESSORIES

- DP10 DESCALER POWDER
- BR55 EB3FX AND EB4FX WALL BRACKET
- FC04 EBFX WATER FILTER FROM 2015

PRODUCT FEATURES

- Convenient push button operation, ideal for front of house and self service
- Lockable mode prevents water being dispensed without the input of a PIN code, perfect for schools, prisons, care homes and settings with vulnerable individuals
- Narrow 250mm footprint saves valuable counter space without compromising capacity or performance
- Built-in water filtration system improves water quality and reduces scale build-up. High volume, easy change FilterFlow cartridge
- Easily operated from a large, colour touchscreen display. Menu navigation is quick and easy with the temperature and timer simple to adjust
- Eco setting reduces the volume of boiling water by 50% for quieter periods. The intelligent predictive eco setting learns usage patterns and switches between eco mode and standard mode to deliver the required hot water output in the most economical way
- 7-day timer allows the boiler to be programmed to switch off overnight or at weekends to conserve energy
- Enhanced diagnostics identify possible causes. The on screen diagnostic information will enable the engineer to identify the parts needed and repair your water boiler at first visit







LINCAT FILTERFLOW COUNTER-TOP AUTOMATIC FILL PUSH-BUTTON WATER BOILER - W 250 MM - 3.0 KW

MODEL: EB3FX/PB

WEIGHTS & DIMENSIONS	
Width	250 mil
Depth	525 mil
Height	596 mil
Weight	14.9 kg

SHIPPING DETAILS	
Ship Width	69.5 cm
Ship Depth	36.6 cm
Ship Height	53 cm
Ship Weight	16.39 kg
Ship Method	Small Parcel (FedEx, UPS, DHL)
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS	
Water Line Required	Yes
Water Connection Source Type	Water Main
Water Inlet Size	0.75 in
Water Inlet Pressure	6 Bar
Drain Line Required	No

PRODUCT CERTIFICATIONS



ENERGY SPECS		
Primary Energy Type	Electric	Electrical Plug T
Electrical Total Amperage	13 A	Number of Elec
Electrical Volts	230V	Electrical Conne
Electrical Total Wattage	3000 W	Number of Elec
Electrical Kilowatts	3 kW	Dedicated Circu
Electrical Phase	1-Phase	Electrical Rema

UK 3-Pin Plug
1_
Cord and Plug
1_
No
Single

ADDITIONAL SPECIFICATIONS	
Capacity (Volume)	15 l
Construction Materials	Stainless Steel
Control Type	Electronic
Hourly Hot Water Output	31
Hourly Number of Hot Cups	155

Rapid Draw Off Hot	111
Rapid Draw Off Hot Cups	55 C
Ventless Cooking Technology	No
Temperature Maximum	98 °C
Temperature Minimum	70 °C

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 24, 2025







LINCAT FILTERFLOW COUNTER-TOP AUTOMATIC FILL PUSH-**BUTTON WATER BOILER - W 250 MM - 3.0 KW**

MODEL: EB3FX/PB

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated March 24, 2025