



UR400G

Glass Door Merchandiser

Product Features

- Hinged glass door
- Electronic thermostat
- Reversible door
- Adjustable shelves
- Fan assisted cooling
- LED interior light with switch
- Digital controller and temperature display
- Adjustable feet with rollers to rear

The UR400G range is available in a white or stainless steel exterior finish to suit your requirement and features a sturdy aluminium door frame. Developed from the solid door UR400 that has a reputation for quality and reliability, this glass door option has fan assisted cooling and vertical LED lighting within the door frame to help create an excellent display for your produce. A digital temperature display and controller help ensure ease of use and reliability.

Total Display Area	m²	0.75
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	85 / 80
Gross / Net Volume	I	374 / 350
Design and Material		
Door Number & Type		1 hinged glass door
Tempered glass		Yes
Door Reversible		Yes
Shelves Number & Type		4 wire shelves white
Shelf Color		White
Shelf Dimensions		505 x 415 mm
Bottom Shelf Dimensions		505 x 220
Max load on Shelves	kg/m²	110
Feet / Legs		4 adjustable feet
Castors		2 rollers
Exterior Finish		White
Interior Finish		White ABS
Interior Light		LED
Lock		Yes
Cooling and Functions		
Type of Controller		Electronic
Type of Cooling		Fan assisted
Type of Defrost		Automatic
Refrigerant		R600a
Refrigerant Refrigerant Charge	g	R600a 75
	g	
Refrigerant Charge Thermometer	g	75
Refrigerant Charge	g	75
Refrigerant Charge Thermometer Power and Consumption	g kWh/24h	75 Yes
Refrigerant Charge Thermometer Power and Consumption Energy Class		75 Yes B
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption	kWh/24h	75 Yes B 2.12
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption	kWh/24h	75 Yes B 2.12 773
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power	kWh/24h	75 Yes 8 2.12 773 13 Amp
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient	kWh/24h kWh/year	75 Yes 8 2.12 773 13 Amp 30°C at 55% RH
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient Input Power	kWh/24h kWh/year W	75 Yes 8 2.12 773 13 Amp 30°C at 55% RH 130
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency	kWh/24h kWh/year W V/Hz	75 Yes 2.12 773 13 Amp 30°C at 55% RH 130 220-240/50
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level	kWh/24h kWh/year W V/Hz	75 Yes 2.12 773 13 Amp 30°C at 55% RH 130 220-240/50
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Dimensions	kWh/24h kWh/year W V/Hz dB(A)	75 Yes 2.12 773 13 Amp 30°C at 55% RH 130 220-240/50 40
Refrigerant Charge Thermometer Power and Consumption Energy Class Energy Consumption Annual Energy Consumption Power Max Ambient Input Power Voltage / Frequency Noise Level Dimensions Internal Dimension (WxDxH)	kWh/24h kWh/year W V/Hz dB(A) mm	75 Yes 8 2.12 773 13 Amp 30°C at 55% RH 130 220-240/50 40



Internal fan

Strong handle