



## Green Single Door Gastronorm Cabinets SPI700 & SNI700



2 YEARS  
WARRANTY



2-3 DAY  
DELIVERY



UK SERVICE  
SUPPORT



MADE IN  
THE EU



### Specifications

| Model   | Type    | Hinge | Capacity<br>Gross / Nett |          | Temperature    | Energy<br>Usage | Dimensions (mm)<br>Width / Depth / Height |     |      | Energy<br>Rating | Refrigerant |
|---------|---------|-------|--------------------------|----------|----------------|-----------------|---|-----|------|------------------|-------------|
| SPI700R | Fridge  | Right | 700 ltrs                 | 461 ltrs | -2°C to +8°C   | 1.5 kW/hr       | 653                                       | 842 | 2040 | C                | R290a       |
| SPI700L | Fridge  | Left  | 700 ltrs                 | 461 ltrs | -2°C to +8°C   | 1.5 kW/hr       | 653                                       | 842 | 2040 | C                | R290a       |
| SNI700R | Freezer | Right | 700 ltrs                 | 461 ltrs | -18°C to -22°C | 5.97 kW/hr      | 653                                       | 842 | 2040 | D                | R290a       |
| SNI700L | Freezer | Left  | 700 ltrs                 | 461 ltrs | -18°C to -22°C | 5.97 kW/hr      | 653                                       | 842 | 2040 | D                | R290a       |

### Key Features

Power supply: 13 amp plug

Castors fitted as standard

Stainless Steel interior and exterior

Shelf dimensions GN2/1

Automatic defrost

Lockable door with replacement gaskets

Intelligent air-circulation system

60mm high-density injected insulation

## Green Single Door Gastronorm Cabinets

### SPI700 & SNI700



2 YEARS  
WARRANTY



2-3 DAY  
DELIVERY



UK SERVICE  
SUPPORT



MADE IN  
THE EU

#### Efficiency

- “Ventilation Gill” on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- Door switch stops the fan when door is opened to avoid cold air exiting the interior, thus saving energy.
- 60 mm thickness, CFC-free, high-density (40 kg/m<sup>3</sup>) polyurethane insulation, injected under high pressure

#### Features

- Fitted with foot pedal and castors. Legs available as an option. Height-adjustable legs available as an option (125mm - 200mm).
- Stamped guides with rounded edges enable more convenient cleaning operations without any difficulties. Placing and adjusting the grids is also easier than ever. Plastic-coated wire grids allow storage of different packaging types and have a maximum loading capacity of up to 40 kg.
- Removable pull-out/ push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Stamped bottom panel with water drain especially designed to make cleaning operations quicker and easier, optimum for hygiene.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.
- 23 grid level positions for increased loading capacity, with a distance of 55mm between them.
- Automatic evaporation of defrost water. Hot gas from the compressor is used to automatically evaporate defrost water, instead of using a heating element, achieving even less energy consumption and reducing the defrosting time by half.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the cabinet to be adapted on-site.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.

#### Contact

**Website:** [www.sterlingpro.co.uk](http://www.sterlingpro.co.uk) / **Phone:** 01264 560190 / **Email:** [sales@sterlingpro.co.uk](mailto:sales@sterlingpro.co.uk)