



The IMC Cirrus 428L Counter Fridge delivers reliable refrigerated storage in a compact undercounter design. Compatible with GN 1/1 gastronorm containers, it features ventilated cooling for even temperature distribution and electronic controls with digital display and alarms for precise temperature management between -2°C and +8°C. A durable 304 stainless steel interior, 441 stainless steel exterior, automatic defrost, automatic condensate evaporation, R290 refrigerant and high-performance cyclopentane insulation ensure efficient, dependable operation. Supplied on lockable castors with two GN 1/1 stainless steel shelves.

AIA FILE NUMBER:

ITEM NUMBER:

PRODUCT FEATURES

- 428L capacity – Generous refrigerated storage for busy commercial kitchens with limited floor space.
- GN 1/1 compatible – Designed to accommodate standard gastronorm containers for efficient food storage.
- Electronic temperature control – Digital controller with alarms provides precise temperature management between -2°C and +8°C.
- Ventilated cooling system – Even air circulation maintains consistent temperatures throughout the cabinet.
- Automatic defrost & condensate evaporation – Minimises maintenance while ensuring reliable refrigeration performance.
- Environmentally friendly refrigerant delivering efficient cooling with a low global warming impact.
- High-performance cyclopentane insulation – CFC and HCFC-free insulation improves temperature retention and reduces energy consumption.
- 304 stainless steel interior – Hygienic, corrosion-resistant and easy to clean for professional foodservice environments.
- 441 stainless steel exterior – Durable construction designed to withstand everyday commercial use.
- Rounded internal corners – Promotes better hygiene by making the cabinet quicker and easier to clean.
- GN 1/1 stainless steel shelves – Strong, durable shelving provides organised and flexible refrigerated storage.



WEIGHTS & DIMENSIONS

Product Width	1,780 mm
Product Depth	700 mm
Product Height	867 mm
Product Dimensions (WxDxH) (mm)	1780 Millimeter X 700 Millimeter X 867 Millimeter

SHIPPING DETAILS

Ship Width	182 cm
Ship Depth	74 cm
Ship Height	100 cm
Ship Weight	155 kg
Shipping Package Type	Pieces

PRODUCT CERTIFICATION ICONS



ENERGY SPECIFICATIONS

Primary Energy Type	Electric
Electrical Volts	230V
Electrical Volts Icon	230V
Electrical Phase Icon	1PH

ADDITIONAL TECHNICAL SPECIFICATIONS

Capacity (Volume)	428
Door Material	Solid
Number of Shelves	2
Temperature Minimum	-2

BIDDING SPECIFICATIONS (SHORT FORM SPECS)

Bidding Specifications Not Available.

TECHNICAL DRAWING

