

LINCAT OPUS PROPANE GAS FREE-STANDING TWIN TANK FRYER -2 BASKETS - W 600 MM - 32.0 KW

MODEL: OG8111/P



Fry delicious food accurately with this Opus 800 Free Standing Twin-Tank Gas Fryer which comes with two independent fryer tanks for greater versatility. Ideal for a variety of busy commercial kitchens, whether it's a large pub or a restaurant, the fryer features convenient piezo ignition and has externally fired heating which allows for easy access for cleaning the tanks.

Opus 800

PRODUCT OPTIONS AND ACCESSORIES

- OF2 Oil filter kit size 2
- LK02 OPUS 350 LEG KIT
- OA8955 SPLASHGUARD FRYERS OPUS 800

PRODUCT FEATURES

- Two independent fryer tanks for greater versatility
- Convenient piezo ignition
- Externally fired heating gives easy access for cleaning tanks







LINCAT OPUS PROPANE GAS FREE-STANDING TWIN TANK FRYER - 2 BASKETS - W 600 MM - 32.0 KW

MODEL: OG8111/P

WEIGHTS & DIMENSIONS	
Width	600 mm
Depth	800 mil
Height	1020 mm
Weight	131.7 kg

SHIPPING DETAILS	
Ship Width	70 cm
Ship Depth	800 cm
Ship Height	122 cm
Ship Weight	144.87 kg
Number of Shipment Parcels	1
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No
Returnable Item	No

PRODUCT CERTIFICATIONS



ENERGY SPECS	
Primary Energy Source Type	Gas
Kilowatts	32 kW
Number of Electrical Conductor Wires	1
Electrical Connection Type	Not Applicable
Electrical Plug Type	Not Applicable
Number of Electrical Plugs	Not Applicable
Dedicated Circuit Required	Yes
Gas Type	Propane

Gas Inlet Size	0.5 in
Gas Inlet Pressure Required	37 mBar
Gas Total BTUs	109189 BTU
Gas Consumption at Max Use Per Hour	2.29 m ³
Total Heat Input at Max Use	32 kW, 109189 BTU per hour
Energy Saving	No

ADDITIONAL SPECIFICATIONS	
Auto Oil Top-Off	No
Basket Lift Type	Not Applicable
Control Type	Mechanical
Food Production Rate	44kg chips - 12mm [frozen], 64kg chips - 12mm [chilled] per hour
Fryer Type	Open Pot
Integrated Filtration	No
Number of Baskets	2
Number of Burners	4

Number of Vats (batteries)	2
Total Oil Capacity (volume)	28
Oil Reclamation	No
Oil Temperature Control	Mechanical
Pumped Oil Filtration	No
Split Pot	Yes
Temperature Maximum	190 °C
Temperature Minimum	90 °C
Vat 1 Oil Capacity (volume)	14
Vat 2 Oil Capacity (volume)	14

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024







MODEL: 0G8111/P


BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING







Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated January 23, 2024

